

## Office of the District Fire Office.

Karnataka State Fire Service

Fire Station

BAGALKOT-587 102 Uate 08/02/2024

## **GOVERNMENT OF KARNATAKA**

## C.NO/107/ADV/DFO/BAGALKOT/2024

To.

Head Master Samuel Memorial English Medium School, Anand Nagar, Mudhol. Bagalkot District.

Sir,

Sub: Issue of 'Fire safety recommendation/Advice' to Samuel Memorial English

Medium Primary and High School at Sy No 521/3B, Mudhol,

Dist - Bagalkot.

Ref: 1) Applicant request letter Dated 05/02/2023

2) No.GBC(2)044/2020-21 Dated 18/06/2022 S.O No.156-B.

\_\*\_\*\_\*\_\*\_\*\_\*\_\*

With reference to the subject above cited, the premises of <u>Samuel Memorial Little Angel's Education Society's</u>, <u>Samuel Memorial English Medium Primary and High School Consisting of Ground Floor & 02 Upper Floors</u>, <u>situated at Sy No 521/3B</u>, <u>Mudhol</u>, <u>Dist Bagalkot</u>, was inspected by me on 05/02/2024 with respect to Fire prevention, Fire fighting and Evacuation measures to be complied in the above premises and has submitted the details as under.

## ANNEXURE-1

(Up to 14.99 mtrs. in height) Group B Education Building

NBC-2016, Part-4, Table 7 (11) 3.1.3 Group B Educational Buildings sub divisionB1& B2. (These condition are indicative and not exclusive all relevant provisions related to fire and life safety of NBC 2016 are mandatory)

A. Details of the building / premises :-

01	Name and Address of the Applicant.	The state of the s	Head Master Samuel Memorial English Medium School, Anand Nagar, Mudhol. Bagalkot District.
02	Name and Address of the premises.		Samuel Memorial Little Angel's Education Society's, Samuel Memorial English Medium Primary and High School ,Sy No 521/3B, Mudhol, Dist Bagalkot.
03	Name and address of the Building owner		Secretary Samuel Memorial Little Angel's Education Society's, Mudhol
04	Number of buildings	1	01Building

05	Number of floors		Ground+02 upper floors			
06	Floor-wise details of occupancy:-					
	Ground Floor	(26) E3) (22) (22)	Class Room-09, Office Room, Principal Room, Staff Room.			
	First Floor	ile 🕏	Class Room-13, Science Lab, Library.			
	Second Floor	100	Class room-08, Auditorium, Computer Lab.			
07	Height of the building		11.40 mtrs			
08	Site area	4	4048.32 Sq Mtr			
09	Built-up area of each floor:-					
	Ground Floor	4	1374.17 Sq. Mtrs.			
	First Floor		1374.17 Sq. Mtrs.			
	Second Floor	1	1374.17 Sq. Mtrs.			
10.	Total built-up area	:	4122.51 Sq. Mtrs.			
11.	Surrounding properties:-					
	East		School Ground.			
	West	1019	Residential Area.			
	North	1	Road.			
	South	:				
12.	Set-back area available around the building :-					
100	East	1	02.00 Mus.			
Sec.	West	DAY D	01.00 11110.			
mich.	North		The state of the s			
		WILESS :	03.00 Mtrs.			
dia	Allowed setbacks (open space) should be maintained free from further obstruction					

Note: Recommended to provide and maintain setbacks as per Local ZR.

POINTO 9

B. On inspection of this Educational premises, the following fire prevention, fire fighting and evacuation measures recommended are considered absolutely essential from fire safety point of view:

Sl. No.	Details (02)	Existing (03)		200	Recommendations (04)
(1)	and the second	The premise is abutting by 06.00			Adequate
01.	Accessibility to the premises	mtrs. Wide hard surfaced road located on Southern side.			Minimum 01 Entrance & 01 Exit Should be Provided.
02.	No. of entrances	01 No entrance of 06.00 mtrs wide is provided.			
	S = 1.88102.64 w	Nos, of staircases	:	02	Recommended to provide
03.	No. of staircases available	Width of staircases	0.50	1.50 mt	staircases maintaining tra-
10			100	30 cm	distance with 22.50 mtrs
		Width of treads			With minimum 02.00 mtrs
		Height of risers		15 cm	Width, 30 cm treads wid
		Nos. of riser per flight		15 no.	

-	Auril Shara - Lil	Height of handrails		.90 mtr	15 cm treads height, 1 mtr.
		Head Room clearance	÷	1.80 mtr	Handrail, with minimum 02.20 head room clearance.
	Portable Fire extinguishers		Not Provided		A. One water mist extinguisher of 9 ltrs capacity should keep near each staircase landing.  B. One mechanical foam extinguisher of 9 ltrs. capacity & One ABC type extinguisher of 6 kgs. capacity should be provided near diesel generator.  C. One CO2 type fire extinguisher, of 4.5 kgs. Capacity should be provided near each electrical panel board & electrical room.  D. One ABC type fire extinguisher of 06 kgs capacity should be located as to be available within 15 mtrs. Radius.
05.	to the second of				One Hose Reel Hose near the staircase (One hose reel hose system for every 1000 Sq. Mt). The hose reel hose of min. 19 mm size and of adequate length to reach the farthest point of each floor should be provided shut off branch having a nozzle of 5mm size. The hose reel hose should be connected at each landing of each building /block/wing/ tower.
06.	Pump at the terrace tank level with minimum pressure of 3.5 kg/cm <sup>2</sup> .	Hasto steed as the TT compare and to Hasto steed as the TT compare and to Hasto streether by compare the process hasto streether the state of the state		The system should be connected to a booster pump of 450 LPM or of 5 HP capacities.	
07.	Diesel Generator	Not Provi	ded		Diesel generator of 15 KVA capacities should be provided to supply alternative power supply.

ESH, CENDER

08.	Terrace tank over respective tower terrace.	Not provided	The system should be connected to an overhead tank of 5,000 ltrs. Capacity and further if basement is provided the tank capacity
	eb and <sup>of</sup> in recognitions.  After construction of an extension of the construction o		shall be increased to 10,000 ltrs. capacity.
	TOTAL TOTAL STATE OF THE STATE	Section in the section of the section in the sectio	(The water tank should be kept exclusively fire fight purpose)  Note: If the existing building is not capable of sustaining the weight of 5,000/10,000 ltrs tank capacity provision shall be made to provide water tank on the side of building with support from ground level by providing RCC column structure or MS column structure.  If there is no option to provide even the above mentioned overhead tank provision shall be made to provide underground water tank of capacity with submersible pump of 5-7 HP capacity.
09.	Escape routes	icotionid dispares, the sediment recommenden are considered.  Continue (03)	Recommended to Provide Direction in which the employees/ Students should have to move in the event of any emergency have been marked with luminous paint at each floor directing the employees towards emergency exits
09.	Fire order (Fire safety plans)	Ser Company of Service	Fire safety plans should be indicated with details of actions to be taken in case of an emergency near staircase landings at each floor with telephone numbers of Mudhol fire station i.e. 08350-283101 & 101 telephone numbers of the nearest Ambulance service &
			4

1000	and the second second second		Police Station.
11.	No smoking board	A CONTRACTOR STATE OF THE STATE	COPTA Sec-4 direction No Smoking area smoking here is an offence board should be written in English & Kannada both language shall be prominently displayed at inside the entry/exit of the each floor.
12.		eless speciale Manna to pro-sky the proven	A Fire Siren shall be installed in the premises to inform the inmates in case of a fire emergency and evacuate the area.
13.	Nominate of Fire Nodal Officer	the land the second sec	A Fire Nodal Officer shall be nominated either from teaching or non teaching staff.
14.	Fire fighting training		At-least 40% of employees shall be got trained in basic fire fighting at R.A.Mundkur fire & Emergency Services Academy, Bannerughatta road, Bangalore within 3 months or at an early date. And shall be submitted to this office.

15. Fire precautionary measures:-

A. Explosive and flammable materials should not be stored in the store room, UPS room, Electrical panel area, class rooms, laboratory & electrical sum panel premises.

- B. Accumulation of combustible waste in and around the premises should be avoided.
- C. The exit ways shall be always kept clear without any obstruction.
- D. Liquefied petroleum gas should not be stored in the building.
- E. The doors shall not be kept locked/latched during working hours and shall be free from obstruction.
- F. During the class hours the class room doors shall not be locked from inside to outside.
- G. As per Hon'ble supreme court order all teachers and staffs shall be trained to handle safety equipment, initiate emergency evacuation and protect their students in the event of fire and other emergency and the school shall observe the Fire Safety Day on April 14<sup>th</sup> of every year by conducting Fire Safety drills with co-ordinate with fire service department.

Under the above circumstance the Karnataka Fire And Emergency Service Department is issuing *Fire Safety Recommendation* to *Samuel Memorial Little Angel's Education Society's, Samuel Memorial English Medium Primary and High School Consisting of Ground Floor & 02 Upper Floors, situated at Sy No 521/3B, Mudhol, Dist Bagalkot.* Subject to condition and compliance of the above recommendations in column 4 of serial B within 03 months compliance to the undersigned.

All requirements recommended above are as per National Building Code-2016 Part-4 clause 3.1.4 of Fire and Life safety will have to be complied with mandatorily.

From the above details it is clear that the 'Management' of the above Educational building have been recommended to provide fire precautionary measures as per National Building Code 2016, Part-4, Table 7 (11) 3.1.3 Group B Educational Buildings Sub division B1 & B2. After full-filling the above recommendations, a Certificate should be obtained by this office. If at any time any of the conditions are found not complied with, this Certificate shall stand withdrawn/cancelled.

The <u>"Fire Safety Recommendation"</u> is valid for a period of **one year** from the date of issue and it is renewable. If above recommendation are fulfilled.

Control of the contro

Yours faithfully

District Fire Officer
Fire Station
BAGALKOT-587 102