

GOVERNMENT OF KARNATAKA

Karnataka State Fire Service
Fire Station
BAGALKOT-587 102

Date 13/06/2025

C.NO/419 /ADV/DFO/BAGALKOT/2025

To.

Head Master Samuel Memorial English Medium School, Anand Nagar, Mudhol. Bagalkot District.

Sir,

Sub: Issue of 'Fire safety recommendation/Advice' to Samuel Memorial English Medium Primary and High School at Sy No 521/3B, Mudhol,

Dist - Bagalkot.

Ref: 1) Applicant request letter Dated: 10/06/2025

2) No.GBC(2)044/2020-21 Dated: 18/06/2022 S.O No.156-B.

With reference to the subject above cited, the premises of Samuel Memorial Little Angel's Education Society's, Samuel Memorial English Medium Primary and High School Consisting of Ground Floor & 02 Upper Floors, situated at Sy No 521/3B, Mudhol, Dist Bagalkot. was inspected by me on 11/06/2025 with respect to Fire prevention, Fire fighting and Evacuation measures to be complied in the above premises and has submitted the details as under.

ANNEXURE-1 (Up to 14.99 mtrs. in height)

Group B Education Building

NBC-2016, Part-4, Table 7 (11) 3.1.3 Group B Educational Buildings sub divisionB1& B2. (These condition are indicative and not exclusive all relevant provisions related to fire and life safety of NBC 2016 are mandatory)

A. Details of the building / premises :-

01	Name and Address of the Applicant.	indt tee	Head Master Samuel Memorial English Medium School, Anand Nagar, Mudhol. Bagalkot District.
02	Name and Address of the premises.	00	Samuel Memorial Little Angel's Education Society's, Samuel Memorial English Medium Primary and High School ,Sy No 521/3B, Mudhol, Dist Bagalkot.
03	Name and address of the Building owner		Secretary Samuel Memorial Little Angel's Education Society's, Mudhol
04	Number of buildings	200	01 Building

0.5	Number of floors		Ground+02 upper floors					
06	Floor-wise details of occupancy:-							
	Ground Floor	1	Class Room-09, Office Room, Principal Room, Staff Room					
	First Floor		Class Room-13, Science Lab, Library.					
	Second Floor		Class room-08, Auditorium, Computer Lab.					
07	Height of the building		11.40 mtrs					
08	Site area		4048.32 Sq Mtr					
00	Built-up area of each floor:-							
	Ground Floor	11	1374 17 Sq. Mtrs.					
	First Floor		1374 17 Sq. Mtrs.					
	Second Floor	1	1374.17 Sq. Mtrs.					
10.	Total built-up area		4122.51 Sq. Mtrs.					
11.	Surrounding properties:-							
	East		School Ground					
	West	1	Residential Area					
	North	1	Road, 06 Mtr wide					
	South	1	Road. 06 Mtr wide					
12.	Set-back area available around the building :-							
	Fast	1	02.00 Mtrs.					
	West	1	01.00 Mtrs.					
	North	10	01.00 Mtrs.					
	South	1	03.00 Mtrs.					
	Allowed setbacks (open space) should be maintained free from further obstruction / construction							

Note: Recommended to provide and maintain setbacks as per Local ZR.

B. On inspection of this Educational premises, the following fire prevention, fire fighting and evacuation measures recommended are considered absolutely essential from fire safety point of view:

SI. No. (1)	Details (02)	Existing (03) The premise is abutting by 06.00 mtrs. Wide hard surfaced road located on Southern side.			Recommendations (04)	
01.	Accessibility to the premises					
02.	No. of entrances	01 No entrance of 06.00 mtrs wide is provided.			Minimum 01 Entrance & 01 Exit Should be Provided.	
03.	No. of staircases available	Nos. of staircases	1:	02	Recommended to provistaircases maintaining trav distance with 22.50 mt	
		Width of staircases	1	1.50 mt		
		Width of treads	1	30 cm		
		Height of risers	:	15 cm	With minimum 02.00 mtrs.	
		Nos. of riser per flight	1:	15 no.	Width, 30 cm treads width, 15	

	himole makers in	Height of handrails	1:	.90 mtr	cm treads height, 1 mtr.
	supplies and 000	Head Room clearance	1:	1.80 mtr	Handrail, with minimum 02.20 head room clearance.
e	Portable Fire extinguishers	Not Provide	ed		A. One water mist extinguisher of 9 ltrs capacity should keep near each staircase landing. B. One mechanical foam extinguisher of 9 ltrs. capacity & One ABC type extinguisher of 6 kgs. capacity should be provided near diesel generator. C. One CO2 type fire extinguisher, of 4.5 kgs. Capacity should be provided near each electrical panel board & electrical room. D. One ABC type fire extinguisher of 06 kgs capacity should be located as to be available within 15 mtrs. Radius.
05.	Hose reel hose system	Not Provided		One Hose Reel Hose near the staircase (One hose reel hose system for every 1000 Sq. Mt). The hose reel hose of min. 19 mm size and of adequate length to reach the farthest point of each floor should be provided shut off branch having a nozzle of 5mm size. The hose reel hose should be connected at each landing of each building /block/wing/ tower.	
06.	Pump at the terrace tank level with minimum pressure of 3.5 kg/cm ² .	Not Provi	ded		The system should be connected to a booster pump of 450 LPM or of 5 HP capacities.
07.		Not Provi			Diesel generator of 15 KVA capacities should be provided to supply alternative power supply.

08.	Terrace tank over respective tower terrace.	Not provided	The system should be connected to an overhead tank of 5,000 ltrs. Capacity and further if basement is provided the tank capacity shall be increased to 10,000 ltrs. capacity.
trail and has been been been been been been been bee	trans on the same of the same		(The water tank should be kept exclusively fire fight purpose) Note: If the existing building is not capable of sustaining the weight of 5,000/10,000 ltrs tank capacity provision
bet. lens mili ags. m	may ad theody man at the large man and the large man at t		shall be made to provide water tank on the side of building with support from ground level by providing RCC column structure or MS column structure. If there is no option to provide
	One Hose Rest Loss certains and the certains and the certains and the certain these certains and the certain	Proceeding of the Committee of the Commi	even the above mentioned overhead tank provision shall be made to provide underground water tank of capacity with submersible pump of 5-7 HP capacity.
09.	Escape routes	Not Provided	Recommended to Provide Direction in which the employees/ Students should have to move in the event of any emergency have been marked with luminous paint at each floor directing the employees towards emergency exits
10.	Fire order (Fire safety plans)	Not Provided	Fire safety plans should be indicated with details of actions to be taken in case of an emergency near staircase landings at each floor with telephone numbers of <i>Mudhol fire station i.e.</i> 08350-283101 & 112, 101 telephone numbers of the nearest Ambulance service & Police Station.

11.	No smoking board	Not Provided	COPTA Sec-4 direction No Smoking area smoking here is an offence board should be written in English & Kannada both language shall be prominently displayed at inside the entry/exit of the each floor.
12.	Fire Siren	Not Provided	A Fire Siren shall be installed in the premises to inform the inmates in case of a fire emergency and evacuate the area.
13.	Nominate of Fire Nodal Officer	Not Provided	A Fire Nodal Officer shall be nominated either from teaching or non teaching staff.
14.	Fire fighting training	Not Provided	At-least 40% of employees shall be got trained in basic fire fighting at R.A.Mundkur fire & Emergency Services Academy, Bannerughatta road, Bangalore within 3 months or at an early date. And shall be submitted to this office.

15. Fire precautionary measures:-

- A. Explosive and flammable materials should not be stored in the store room, UPS room, Electrical panel area, class rooms, laboratory & electrical sum panel premises.
- B. Accumulation of combustible waste in and around the premises should be avoided.
- C. The exit ways shall be always kept clear without any obstruction.
- D. Liquefied petroleum gas should not be stored in the building.
- E. The doors shall not be kept locked/latched during working hours and shall be free from obstruction.
- F. During the class hours the class room doors shall not be locked from inside to outside.
- G. As per Hon'ble supreme court order all teachers and staffs shall be trained to handle safety equipment, initiate emergency evacuation and protect their students in the event of fire and other emergency and the school shall observe the Fire Safety Day on April 14th of every year by conducting Fire Safety drills with co-ordinate with fire service department.

Under the above circumstance the Karnataka Fire And Emergency Service Department is issuing *Fire Safety Recommendation* to Samuel Memorial Little Angel's Education Society's, Samuel Memorial English Medium Primary and High School Consisting of Ground Floor & 02 Upper Floore, situated at Sy No: 521/3B, Mudhol, Dist Bagalkot.

Subject to condition and compliance of the above recommendations in column 4 of serial B within 03 months compliance to the undersigned.

♣All requirements recommended above are as per National Building Code-2016 Part-4 clause 3.1.4 of Fire and Life safety will have to be complied with mandatorily.

From the above details it is clear that the 'Management' of the above Educational building have been recommended to provide fire precautionary measures as per National Building Code 2016, Part-4, Table 7 (11) 3.1.3 Group B Educational Buildings Sub division B1 & B2. After full-filling the above recommendations, a Certificate should be obtained by this office. If at any time any of the conditions are found not complied with, this Certificate shall stand withdrawn/cancelled.

The <u>"Fire Safety Recommendation"</u> is valid for a period of one year from the date of issue and it is renewable. If above recommendation are fulfilled.

CAN CONTROL TO THE STATE OF THE

Your's faithfully

Pistrict Fire Officer
Fire Station
BAGALKOT-587 102